

## MAL Bravo 502

### RETAINED FIREFIGHTER ALERTER

#### 21st Century systems for the Fire Service

The MAL range of equipment is dedicated exclusively to meet Fire Service needs



- ◆ **PC programming** 'shoes' may be linked to simultaneously program multiple alerters
- ◆ **Text Messages:** Although a numeric pager, four pre-programmed pseudo text messages can be activated by function code. E.g. Fire, Test, Co-respond, CSU, Etc
- ◆ **Loud Alert Tone:** Can be heard in high ambient noise environments
- ◆ **Urgent Alert:** an alternating audible two tone and vibrate alert allocated to a priority cap code and call type to over-ride any other call, e.g. FIRE
- ◆ **Backlight:** LCD is lit on receipt of a message
- ◆ **Time & Date Display:** Furthermore, messages are time & date stamped and there is a Daily Alarm function.

# TECHNICAL SPECIFICATION

## MAL Bravo 502 — Retained Fire fighter Alerter

- ◆ Radio Identity Codes Four (4) each with four function codes
- ◆ Frequency 136—174 MHz
- ◆ Code Format CCIR N° 1 (POCSAG)
- ◆ Sensitivity - 107dBm (front)
- ◆ EIA Selectivity 55dB at ±25kHz
- ◆ EIA Spurious & Image 50dB
- ◆ Operating Temperature -10°C to +50°C
- ◆ Battery Single Alkaline AAA
- ◆ Battery life > 28 days with 10 calls a day
- ◆ Weight (with battery) 45 grams
- ◆ Dimensions 64 x 43 x 19.5 mm



**Cyfas Systems Limited**  
Unit 5 Ivel Road Business  
Park , 1 Ivel Road  
Shefford , Beds SG17 5JU  
Tel 01462 818880  
[www.cyfas.co.uk](http://www.cyfas.co.uk)  
Email [Sales@cyfas.co.uk](mailto:Sales@cyfas.co.uk)